

PROgrommet™

Cost effective stormwater connections



Introducing the new Vinidex PROgrommet™ range of stormwater service connections.

A quick and easy system to install 100mm and 150mm connections to StormPRO® stormwater pipe up to 900mm nominal diameter.

- Save time and money
- No more cutting in junctions
- Connects PVC smooth wall pipe to StormPRO®
- Simple procedure using the PROsaw™
- Watertight seal
- Manufactured from EPDM rubber
- No mortar or sealant required

PROgrommet™ Range

StormPRO® Nominal Diameter	Service Connection Diameter	
	100mm	150mm
225mm	30185	30188
300mm		
375mm	30186	30177
450mm		
525mm		
600mm	30178	30178
750mm		
900mm		

PROsaw™ Range

Service Connection Diameter	
100mm	150mm
30231	30232

USER INSTRUCTIONS

1. Drill hole in StormPRO Pipe as per User Instructions of PROsaw
2. Inspect engraving on PROgrommet to ensure the correct size for selected StormPRO Pipe.
3. Present PROgrommet to hole with Grommet flange to the inside and locating wings to the outside of the StormPRO Pipe
4. Squash the PROgrommet by hand whereby the two locating wings align in the centre.
5. With the flattened PROgrommet form a “C” shape and offer it to the prepared hole
6. Position locating wings in the valley of the StormPRO Pipe profile
7. Apply Vinidex Lubricant to the inside diameter of the PROgrommet
8. Cut lead-in chamfer on pipe which is to be offered to PROgrommet.
9. Mark a line on pipe showing the required insertion depth
10. Apply Vinidex Lubricant to outside diameter of pipe
11. Insert prepared pipe to pre-marked insertion depth

