

# PROsaw™

Quick PROgrommet installation



Specifically designed for simple installation of the new Vinidex PROgrommet™ range of stormwater service connections.

A quick and easy system to install 100mm and 150mm connections to StormPRO® stormwater pipe up to 900mm nominal diameter.

- Save time and money
- No more cutting in junctions
- Connects PVC smooth wall pipe to StormPRO®
- Watertight seal
- No mortar or sealant required

## PROgrommet™ Range

StormPRO® Nominal Diameter	Service Connection Diameter	
	100mm	150mm
225mm	30185	30188
300mm		
375mm	30186	30177
450mm		
525mm		
600mm	30178	30178
750mm		
900mm		

Service Connection Diameter	
100mm	150mm
30231	30232

## PROsaw™ Range



USER INSTRUCTIONS

1. Mark desired centre point for hole on StormPRO Pipe
2. Hole centre **MUST** be in the centre of pipe profile valley
3. Attach PROsaw to **LOW SPEED HIGH TORQUE** drill  
Safety Glasses must be worn for all drilling operations
4. Present PROsaw to marked centre point and complete drilling pilot hole
5. Select low speed for trepanning operation. For 127mm PROsaw select 200 RPM, for 184mm PROsaw select 135 RPM
6. Grip drill with two hands with one hand on screw-in handle attachment
7. As PROsaw approaches profile pipe ensure saw is square with pipe profile and cutting commences evenly on both sides
8. Complete trepanning operation and remove centre slug from PROsaw
9. Deburr hole to remove plastic swarf
10. Insert PROgrommet ensuring locating wings fit into StormPRO Pipe profile