Version number 142 (replaces version 141) Printing date 19.08.2022 Revision: 19.08.2022

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: DUR CLEANER TI 500ML\*12 L39
- · CAS Number:

78-93-3

· EC number:

201-159-0

· Index number:

606-002-00-3

- Registration number 01-2119457290-43
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer(1)/Supplier(2):

**Bison International** Vinidex Dr.A.F.Philipsstraat 9 4-26 College St NL-4462 EW Goes Darlinghurst PO Box 160 NSW 2010

NL-4460 AD Goes Ph: 02 8278 0500(business hours)

tel. +31 88 3235700 Emergency Contact - 131 126 Poisons Information Centre fax. +31 88 3235800

www.vinidex.com.au e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GR-FN

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

Hazard pictograms

(Contd. of page 1)





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

butanone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

- Additional information:
- EUH066 Repeated exposure may cause skin dryness or cracking.
- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

butanone

· Hazard statements

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 3)

- GB-EN

#### 6120125 - DUR CLEANER TI 500ML\*12 L39

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 2)

Determination of endocrine-disrupting properties

List II

#### **SECTION 3: Composition/information on ingredients**

- · 3.1 Substances
- · CAS No. Description

78-93-3 butanone

- · Identification number(s)
- EC number: 201-159-0
- · Index number: 606-002-00-3

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

GB-EN

(Contd. on page 4)

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 3)

#### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

#### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

#### · DNELs

#### 78-93-3 butanone

| Oral       | Consumer, oral, longterm exposition       | 31 mg/kg bw/day  |
|------------|---|------------------|
| Dermal     | Consumer, dermal, longterm exposition     | 412 mg/kg bw/day |
| Inhalative | Consumer, inhalation, longterm exposition | 106 mg/m³        |

(Contd. on page 5)

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 4)

|                           | (Contd. of page 4               |  |
|---------------------------|---------------------------------|--|
| · PNECs                   |                                 |  |
| 78-93-3 but               | anone                           |  |
| Fresh water               | 55.8 mg/l                       |  |
| Marine wate               | er 55.8 mg/l                    |  |
| Soil                      | 22.5 mg/kg                      |  |
| · Ingredients             | s with biological limit values: |  |
| 78-93-3 but               | anone                           |  |
| BMGV 70 p                 |                                 |  |
|                           | Medium: urine                   |  |
| Sampling time: post shift |                                 |  |
| Par                       | Parameter: butan-2-one          |  |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- Recommended filter device for short term use: Filter A
- · Hand protection

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

**Body protection:** Solvent resistant protective clothing

GB-FN

(Contd. on page 6)

Version number 142 (replaces version 141) Revision: 19.08.2022 Printing date 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 5)

| SECTION | 9. Phy  | vsical | and | chemical | properties |
|---------|---------|--------|-----|----------|------------|
|         | J. I II | voicai | ana | CHCHICA  |            |

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Odour: Like ketone · Odour threshold: Not determined. -86.3 °C

Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 79-80.5 °C · Flammability Highly flammable.

Lower and upper explosion limit

1.8 Vol % · Lower: · Upper: 11.5 Vol % -9 °C · Flash point: · Ignition temperature: 514 °C

Not determined. Decomposition temperature: · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C: 0.4 mPas

Solubility

water at 20 °C: 290 g/l

Partition coefficient n-octanol/water (log

Not determined. Vapour pressure at 20 °C: 105 hPa

Density and/or relative density

Density at 20 °C: 0.804-0.807 g/cm<sup>3</sup> Not determined. · Relative density Not determined. · Vapour density

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

**Auto-ignition temperature:** Not determined.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Organic solvents: 100.0 % · Solids content: 0.0 % · Molecular weight 72.11 g/mol

Change in condition

· Evaporation rate Not determined.

(Contd. on page 7)

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 6)

|  | (Conta. or page o)                  |  |
|--|-------------------------------------|--|
| · Information with regard to physical haza | ard                                 |  |
| classes                                    |                                     |  |
| · Explosives                               | Void                                |  |
| Flammable gases                            | Void                                |  |
| Aerosols                                   | Void                                |  |
| · Oxidising gases                          | Void                                |  |
| · Gases under pressure                     | Void                                |  |
| Flammable liquids                          | Highly flammable liquid and vapour. |  |
| Flammable solids                           | Void                                |  |
| Self-reactive substances and mixtures      | Void                                |  |
| · Pyrophoric liquids                       | Void                                |  |
| Pyrophoric solids                          | Void                                |  |
| Self-heating substances and mixtures       | Void                                |  |
| Substances and mixtures, which emit        |                                     |  |
| flammable gases in contact with water      | Void                                |  |
| Oxidising liquids                          | Void                                |  |
| Oxidising solids                           | Void                                |  |
| Organic peroxides                          | Void                                |  |
| · Corrosive to metals                      | Void                                |  |
| · Desensitised explosives                  | Void                                |  |
|  |                                     |  |

#### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 78-93-3 butanone

Oral LD50 3300 mg/kg (rat)
Dermal LD50 5000 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

(Contd. on page 8)

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 7)

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

List II

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

GB-EN

(Contd. on page 9)

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 8)

| ADR/ADN  IMDG, IATA  I193 ETHYL METHYL KETONE (METHYL ETHYL KETONE) ETHYL METONE)  14.3 Transport hazard class(es)  ADR/ADN  Class Label  3 (F1) Flammable liquids. 3 (F1) Flammable liquids. 3 Flammable liquids. 5 Flammable liquids. 6 Flammable liquids. 7 Flammable liquids. 8 Flammable liquids. 9 Flammable liquids. 14.4 Packing group 14.5 Environmental hazards: 8 Marine pollutant: 14.6 Special precautions for user 14.6 Special precautions for user 14.6 Special precautions for user 14.7 Maritime transport in bulk according to limitation umber (Kemler code): 15 Flammable liquids. 16 Flammable liquids. 17 Flammable liquids. 18 Flammable liquids. 19 Flammable liquids. 10 Flammable liquids. 10 Flammable liquids. 10 Flammable liquids. 10 Flammable liquids. 11 Flammable liquids. 11 Flammable liquids. 12 Flammable liquids. 13 Flammable liquids. 13 Flammable liquids. 14 Flammable liquids. 16 Flammable liquids. 17 Flammable liquids. 18 Flammable liquids. 19 Flammable liquids. 10 Flammable liquids. 10 Flammable liquids. 11 Flammable liquids. 12 Flammable liquids. 13 Flammable liquids. 14 Flammable liquids. 15 Flammable liquids. 16 Flammable liquids. 16 Flammable liquids. 16 Flammable liquids. 17 Flammable liquids. 18 Flammable liquids. 19 Flammable liquids. 10 Flammable liqu | 14.1 UN number or ID number<br>ADR/ADN, IMDG, IATA        | UN1193   |
|--|---|--|
| 14.3 Transport hazard class(es)  ADR/ADN  Class Label 3 (F1) Flammable liquids. 4 (F1) Flammable liquids. 4 (F2) Flammable liquids. 4 (F2) Flammable liquids. 4 (F2) Flammable liquids. 4 (F3) Flammable liquids. 5 (F3) Flammable liquids. 6 (F3) Flammable liquids. 6 (F3) Flammable liquids. 7 (F3) Flammable liquids. 7 (F3) Flammable liquids. 8 (F3) Flammable liquids. 9 (F3) Flammable | 14.2 UN proper shipping name ADR/ADN IMDG, IATA           | 1193 ETHYL METHYL KETONE (METHY<br>ETHYL KETONE)<br>ETHYL METHYL KETONE (METHYL ETHY                 |
| Class  | ,   |  |
| Class 3 (F1) Flammable liquids.  3 IMDG, IATA  Class 3 Flammable liquids. 3 14.4 Packing group ADR/ADN, IMDG, IATA II  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user Hazard identification number (Kemler code): 33 EMS Number: F-E,S-D Stowage Category B  14.7 Maritime transport in bulk according to IMO instruments Not applicable.  Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 miles  | 14.3 Transport hazard class(es)                           |  |
| Label 3  IMDG, IATA  Class 3 Flammable liquids. 3  14.4 Packing group ADR/ADN, IMDG, IATA  II  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user Hazard identification number (Kemler code): 33 EMS Number: Stowage Category B  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml   | ADR/ADN   |  |
| Class Label 3  14.4 Packing group ADR/ADN, IMDG, IATA II  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user Hazard identification number (Kemler code): 33 EMS Number: F-E,S-D Stowage Category B  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  | Class<br>Label  |  |
| Label 3  14.4 Packing group ADR/ADN, IMDG, IATA II  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 33 EMS Number: F-E,S-D Stowage Category B  14.7 Maritime transport in bulk according to IMO instruments Not applicable.  Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  | IMDG, IATA  |  |
| ADR/ADN, IMDG, IATA  14.5 Environmental hazards: Marine pollutant:  No  14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml   | Class<br>Label  | ·  |
| Marine pollutant:  14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  | 14.4 Packing group<br>ADR/ADN, IMDG, IATA                 | II   |
| Hazard identification number (Kemler code): 33 EMS Number: F-E,S-D Stowage Category B  14.7 Maritime transport in bulk according to IMO instruments Not applicable.  Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  | 14.5 Environmental hazards:<br>Marine pollutant:          | No   |
| EMS Number: Stowage Category  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml   |   |  |
| Stowage Category  14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml   |   |  |
| 14.7 Maritime transport in bulk according to IMO instruments  Transport/Additional information: Quantity limitations  On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ)  Excepted quantities (EQ)  Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  |   |  |
| Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  |   | <del>-</del>   |
| Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)  IL Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml  |   | Not applicable.  |
| Limited quantities (LQ)  Excepted quantities (EQ)  Code: E2  Maximum net quantity per inner packaging: 30 m  Maximum net quantity per outer packaging: 50 ml   | Transport/Additional information:<br>Quantity limitations | On passenger aircraft/rail: 5 L  |
| Limited quantities (LQ)  Excepted quantities (EQ)  Code: E2  Maximum net quantity per inner packaging: 30 m  Maximum net quantity per outer packaging: 50 ml   | ADR/ADN   |  |
| Maximum net quantity per inner packaging: 30 m<br>Maximum net quantity per outer packaging: 50<br>ml   | Limited quantities (LQ)                                   |  |
| Transport category 2   |   | Maximum net quantity per inner packaging: 30 m<br>Maximum net quantity per outer packaging: 50<br>ml |
|  | Transport category  | 2  |

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

|                            | (Contd. of page 9   |
|----------------------------|---|
| · Tunnel restriction code  | D/E   |
| ·IMDG                      |   |
| · Limited quantities (LQ)  | 1L  |
| · Excepted quantities (EQ) | Code: E2  |
|                            | Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500  |
| · Remarks:                 | ml Under certain conditions substances in Class 3 (flammable liquids) can be classified ir packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2 |
| · UN "Model Regulation":   | UN 1193 ETHYL METHYL KETONE (METHYL<br>ETHYL KETONE), 3, II   |

#### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

Substance is not listed.

- · REGULATION (EU) 2019/1148
- · Regulation (EC) No 273/2004 on drug precursors

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: Bison QESH
- Contact: Reach coordinator

(Contd. on page 11)

#### 6120125 - DUR CLEANER TI 500ML\*12 L39

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.08.2022 Version number 142 (replaces version 141) Revision: 19.08.2022

Trade name: DUR CLEANER TI 500ML\*12 L39

(Contd. of page 10)

- Date of previous version: 28.06.2022 · Version number of previous version: 141
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

GB-EN