




Philmac Metric EasyLOK[®] Fittings

Procedure



1. Cut Pipe Square

Clean the pipe end and ensure it is free from burrs. Chamfering or lubrication of pipe is not required.



2. Ready to Use Position

The fitting is pre-assembled and ready to use, however always ensure that 3 threads are showing before proceeding. Check that fitting body is lubricated - use water or CRC lubricant if required.



3. Witness Mark the Pipe

the ready to use position lay the pipe against the fitting with the end of the pipe lined up with the flange of the body. Witness mark the section of pipe that is alongside the nut opening.



4. Pipe Insertion

Insert the pipe up to the witness mark, or if not using a witness mark until the first point of resistance is felt.



5. Nut Tightening

The nut should be tightened by hand and then firmly with a wrench. Tighten the nut all the way to the flange on the body of the fitting.



6. Fully Installed

The fitting is now fully installed.

Limitation of Liability

This product catalogue has been compiled by Vinidex Pty Limited ('the Company') to promote better understanding of the technical aspects of the Company's products to assist users in obtaining from them the best possible performance.

The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is supplied subject to acknowledgement of the following conditions: The product catalogue is protected by copyright and may not be copied or reproduced in any form or by any means in whole or in part without prior consent in writing by the Company. 2 Product specifications, usage data and advisory information may change from time to time with advances in research and field experience. The Company reserves the right to make such changes at any time without further notice. 3 Correct usage of the Company's products involves engineering judgements, which can not be properly made without full knowledge of all the conditions pertaining to each specific installation. The Company expressly disculations all and any liability to any preson whether supplied with this publication or not in respect of anything and all of the consequences of anything done or omitted to be done by any such person in reliance whether whole or part of the contents of this publication. 4 No offer to trade, nor any conditions of trading, are expressed or implied by the issue of content of this product catalogue. Nothing herein shall override the Company's Sales Office of the Company's This product catalogue is abaltermain the property of the Company, and shall be surrendered on demand to the Company's 6 Information supplied in this product catalogue does not override ajob specification, where such conflict arises; consult the authority supervising the job. © Copyright Vinidex Pty Limited.