

Type P Green Solvent Cement

for reliable, leak-proof jointing of PVC pressure pipes

Vinidex Type P solvent cement is a specially formulated resin-based adhesive for joining PVC pipe and fittings. It is slower setting than Type N and suited for pressure applications in residential, commercial and industrial work such as water supply, irrigation and pools.

PART OF THE VINIDEX PIPE JOINTING FLUIDS FAMILY

- Conforms to AS/NZS 3879
- AS/NZS 4020 approved - suitable for use in contact with drinking water
- Watermark and ISO 9001:2008 accredited
- All packaging is Dangerous Goods approved
- Engineered cap to minimise the risk of leaks
- Range of sizes to suit any job
- Supplied with a natural bristle brush applicator cap for easy application
- Proven product performance over several decades in applications around Australia and overseas
- 2 year shelf life if unopened and stored in a cool, dry, well ventilated place out of direct sunlight



Technical Data

Size Range	125ml – 4L
Manufacturing Standard	AS/NZS 3879
Quality Management System	ISO 9001
Certificate Number	QEC0570 (SAI Global)

INGREDIENT	% WEIGHT
Methyl ethyl ketone	10 - 30
Cyclohexanone	10 - 30
Tetrahydrofuran	10 - 30
N-methyl-2-pyrrolidone	<5

DRYING TIME	JOINT STRENGTH TO EXCEED
20 minutes	0.5 MPa
1 day	3 MPa
60 days	8 MPa

Product Range

Vinidex Code	Volume	Min. (Pack) Quantity	Carton Quantity
82420	125ml	1	36
82422	250ml	1	36
82424	500ml	1	20
82426	1L	1	12
82428	4L	1	4

Product Application

Nominal Diameter DN	APPROXIMATE NUMBER OF JOINTS PER 500ml	
	Priming Fluid	Solvent Cement
15	1050	300
20	625	175
25	450	130
32	325	95
40	250	70
50	150	42
65	125	35
80	100	30
100	70	25
125	60	20
150	45	15
200	25	12
225	15	7
250	12	6
300	12	5
375	8	5