

PVC Slotted Stormwater Pipe SCJ

PVC slotted stormwater pipe with solvent cement joints (SCJ)
DN90 to DN300 manufactured to AS/NZS 1254

Vinidex uses both virgin and recycled raw materials to manufacture sustainable stormwater pipe systems. The economic advantages of Vinidex stormwater pipes and fittings, combined with their light weight, ease of installation and reliable performance, makes PVC the material of choice for stormwater applications in Australia.

PART OF THE STORMWATER SYSTEMS RANGE

- Manufactured in Australia
- Solvent cement joint
- Available in 6m effective lengths
- Meets the clear water opening requirements of AS 2439.1 for Type 2 pipe (not less than 1500mm² per metre of pipe)
- Light weight and easy to handle
- Suitable for aggressive or saline soils
- Range of compatible [PVC fittings](#) available



Applications

- Non-pressure stormwater drainage
- Below ground stormwater drainage in buildings and infrastructure

Technical Data

Size Range	DN90 – DN300
Manufacturing Standard	AS/NZS 1254
Best Environmental Practice	BEP-PVC 570
Quality Management System	ISO 9001
Certificate Number	QEC0570 (SAI Global)

ITEM	DESCRIPTION
Pipe material	PVC-U
Colour	White
Joint type	Solvent cement
Solvent cement type	Type N (blue)





Dimensions

Nominal Diameter DN	Outside Diameter		Tmean (mm)	ID (mm)
	Dm min (mm)	Dm max (mm)		
90	90.0	90.3	1.6	87.0
150	160.0	160.5	2.9	154.5
225	250.0	250.7	4.3	241.8
300	315.0	315.9	5.7	304.1

Product Range

Vinidex Code	Nominal Size DN (mm)	Length L (m)	Crate Quantity
20670	90	6	72
20710	150	6	26
20720	225	6	12
20730	300	6	6