

PE Communications Conduit SDR12

PE white coextruded continuous conduit Compatible with Series 1 pressure pipe outside diameters DN63 to DN110 manufactured to AS/NZS 4130 dimensions

Vinidex PE communications conduits are used to enclose and protect cables and wiring for communications applications. Along with conduits and ducts, the Vinidex range includes fittings, cable covers, marking tapes, pits and accessories to provide a complete cable management system.

PART OF THE ELECTRICAL & COMMUNICATIONS SYSTEMS RANGE

- Manufactured in Australia
- SDR12 wall thickness
- Available in coils
- Improved material performance
- IP rating of 67
- Light weight and easy to handle
- Suitable for aggressive or saline soils
- Range of compatible fittings available



Applications

- Telstra, NBN and other data or communications projects
- Sub-duct or direct burial

Technical Data

Size Range DN63 – DN110

Manufacturing Standard AS/NZS 4130 (dimensions only)

Quality Management System ISO 9001

Certificate Number QEC0570 (SAI Global)

ITEM	DESCRIPTION		
Pipe material	PE100		
Colour	White coextruded outer layer over black wall		
Joint type	Varies		





Dimensions

Nominal Size DN	SDR	Outside	Diameter	-	ID (mm)
		De min (mm)	De max (mm)	Tmean (mm)	
63	12	63.0	63.6	5.3	53
110	12	110.0	111.0	9.2	92

Product Range

Vinidex Code	Telstra Approved		Length (m)	Class	SDR	Colour	Min. Quantity
		(mm)					