
AKASISON ROOF OUTLET XL75 FOR CONCRETE GUTTER CLAD

ARTICLE CODE: 747803





According to EN 1253

Roof outlet for gutter for Akasison siphonic roof drainage systems. With holes for application in concrete gutter clad.

Delivery includes: Air baffle with integrated leaf guard (UV-stabilized).

Connection to HDPE, clamp flange and knock-in bolts.

Application: Concrete gutter clad.

Insulation thickness: n.a

Connection to HDPE: Electrofusion coupler d75 mm Code 410795.

Dimensions: d1 = 75 mm.

L = 55 mm. S = 120 mm. A = 180 mm. $\emptyset \square 110$ mm.

Drilling core size: $\emptyset \square$ 110 mm. Performance: 1-18,0 l/s.

Material: ASA, stainless steel, PVC, HDPE.

Code	Туре	Description	Weight (kg)
747803	Akasison XL75 CON COV	Concrete gutter clad	0,97

Water level*	25 mm	30 mm	35 mm	40 mm	45 mm	50 mm	55 mm
Performance [l/s]	7,0	11,7	13,9	17,4	18,0	18,0	18,0

^{*} height measured from the underside of the leaf guard

Packaging: 1 piece Discount group: AD

Date: 02.2021



