
## **AKASISON ROOF OUTLET XL75 FOR CONCRETE GUTTER**

## **ARTICLE CODE: 747801**





## According to EN 1253

Roof outlet for gutter for Akasison siphonic roof drainage systems. With holes for application in concrete gutter.

Delivery includes: Air baffle with integrated leaf guard (UV-stabilized).

Connection to HDPE and knock-in bolts.

Application: Concrete gutter.

Insulation thickness: n.a

Connection to HDPE: Electrofusion coupler d75 mm Code 410795.

Dimensions: d1 = 75 mm.

L = 55 mm. S = 120 mm. A = 180 mm.  $\emptyset \square 110$  mm.

Drilling core size:  $\emptyset \square 110 \text{ n}$ Performance: 1-18,0 l/s.

Material: ASA, stainless steel, PVC, HDPE.

Code	Туре	Description	Weight (kg)
747801	Akasison XL75 CON	Concrete gutter	0,91

Water level*	25 mm	30 mm	35 mm	40 mm	45 mm	50 mm	55 mm
Performance [l/s]	7,0	11,7	13,9	17,4	18,0	18,0	18,0

<sup>\*</sup> height measured from the underside of the leaf guard

Packaging: 1 piece Discount group: AD

Date: 02.2021



